

Vuquest 3330g

OEM Fixed-Mount 2D Area Imager

Honeywell's Vuquest 3330g OEM 2D imager offers aggressive scanning of all 1D and 2D barcodes in a durable and flexible form factor designed to accelerate integration into your solutions. Incorporating Honeywell's advanced decoding technology, Vuquest 3330g is optimized for reading barcodes directly off mobile phone screens and is ideal for customer-facing applications such as self-service kiosks, vending machines, ATMs, access control, retail POS and fast food self-ordering kiosks.

Designed for OEM fixed mount and kiosk integrations, the 3330g is easy to install onto a bracket, is available with multiple interfaces, and supports presentation mode scanning—all capabilities that make it easy to tailor to your environment. Honeywell's TotalFreedom software plug-ins expand the capabilities of 3330g, enabling OCR capture and reading, driving license parsing, boarding pass scanning and more.

Ready for ever-changing data capture needs, the 3330g can be incorporated into your design as a 1D-only device, and then affordably upgraded to 2D scanning at any time in the future. This upgradeability freedom protects your investment and can extend your product lifecycles, allowing you to match new market and customer requirements without costly redesigns.



Delivering high scanning throughput and remote configurability in an easy-to-mount enclosure, the Vuquest 3330g is the smart way to add 2D imaging performance to your product design.

Relying on an LED-aiming solution that is completely laser-free, the 3330g is perfect for customer-facing environments where barcode scanning solutions are used by the end customer. Easy to install, flexible, and upgradeable: Vuquest 3330g is the ideal OEM imager for your fixed-mount solution.

FEATURES & BENEFITS



Superior 1D and 2D barcode reading performance, whether on paper or mobile phone screens.



Its compact size, multiple interfaces, and ease of mounting make 3330g flexible to fit your design requirements.



Protect your investment and extend your product lifecycles with the ability to enable 2D scanning at any point in the future.



Simplify support needs and enjoy reduced total cost of ownership by remotely managing installed devices.



Laser-free aiming is ideal for customer-facing environments and eliminates any risk of eye injury.

Vuquest 3330g Technical Specifications

MECHANICAL

Dimensions (LxWxH):

74 mm x 50 mm x 26 mm (2.9" x 1.9" x 1.0")

Weight: 75g (2.7 oz)

Termination: 15-POS D-Sub connector

ELECTRICAL

Input Voltage: 5 VDC \pm 0.25 V

Operating Power: 2.3 W (450 mA @ 5 V)

Standby Power: 0.45 W (90 mA @ 5 V)

Host System Interfaces: USB, RS232, and Keyboard Wedge

ENVIRONMENTAL

Operating Temperature:

0°C to 40°C (32°F to 104°F)

Storage Temperature:

-20°C to 70°C (-4°F to 158°F)

Humidity: 5% to 95% relative humidity, non-condensing

Drop: Designed to withstand 1.5 m (5') drops

Vibration: Withstands 5G peak from 22 to 300 Hz

Environmental Sealing: IP53

Light Levels:

0 to 100,000 lux (9,290 foot-candles)

ESD Tolerance: Up to 15kV direct air, up to 8kV indirect coupling plane

SCAN PERFORMANCE

Sensor: Proprietary Honeywell sensor

Scan Pattern: Area Image (844 x 640 pixel array)

Motion Tolerance: Up to 240 in/s for UPC 13 mil (in Enhanced Streaming Presentation Trigger Mode)

Scan Angle:

Horizontal: 42.4°

Vertical: 33°

Focal Point: 127 mm (5')

Print Contrast:

20% minimum reflectance difference

Pitch, Skew : \pm 45°, \pm 65°

SYMBOLOGIES SUPPORTED

Linear: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post

2D Stacked: PDF417, MicroPDF417, GS1 Composite

2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code
Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code

OCR Option: OCR-A, OCR-B, E13B (MICR)

WARRANTY

2 year factory warranty

DEPTH OF FIELD TYPICAL PERFORMANCE

SYMBOLGY	STANDARD RANGE (SR)	HIGH DENSITY (HD)
5 mil Code 39	55 mm – 159 mm (2.16" - 6.26")	22 mm – 125 mm (.87" - 4.92")
13 mil UPC	39 mm – 435 mm (1.53" – 17.13")	30 mm – 190 mm (1.18" – 7.48")
10 mil Data Matrix	47 mm – 216 mm (1.85" - 8.50")	16 mm – 142 mm (.63" - 5.59")
20 mil Data Matrix	33 mm – 414 mm (1.30" – 16.30")	19 mm – 209 mm (.75" – 8.23")

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies.

Honeywell Sensing & Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

www.honeywell.com

Vuquest 3330g OEM Fixed-Mount 2D Area Imager DS Rev A 12/15
© 2015 Honeywell International Inc.

Honeywell