

TP9550

5 MP Smart Code Reader



Introduction

TP9550 smart code reader can read different types of codes with reading speed up to 90 codes/sec. It adopts Tipcode's deep learning algorithm to process images with good robustness, and can recognize various complex codes.

Key Feature

- Adopts built-in deep learning algorithm to read codes with good robustness.
- Adopts CMOS global shutter sensor to provide high quality images.
- Adopts mechanical autofocus lens to achieve automatic focusing.
- Supports code score and quality evaluation for code printing quality.
- Adopts controllable light source design providing diversified light.
- Ingress protection rating 67.

Applicable Industry

Consumer electronics, food and beverage, pharmaceutical, semiconductor, automobile, new energy, etc.

Available Model


8 mm focal length: TP9550-08S-WBN

12 mm focal length: TP9550-12S-WBN

16 mm focal length: TP9550-16S-WBN

25 mm focal length: TP9550-25S-WBN

Dimension




Specification

Model	TP9550-08S-WBN	TP9550-12S-WBN	TP9550-16S-WBN	TP9550-25S-WBN
Performance				
Symbologies	1-dimensional codes: Code 39, Code 93, Code 128, CodaBar, EAN 8, EAN 13, UPCA, UPCE, ITF 14, ITF 25, Matrix 25, MSI, China Post, Code 11, and Industrial 25			
	2-dimensional codes: QR Code, Data Matrix			
	Stack codes: PDF 417			
Max. frame rate	40 fps			
Max. reading speed	90 codes/sec			
Sensor type	CMOS, global shutter			
Pixel size	3.2 μm × 3.2 μm			
Sensor size	1/1.7"			
Resolution	2560 × 2048			
Exposure time	60 μs to 1 sec			
Gain	0 dB to 18 dB			
Mono/color	Mono			
Communication protocol	SmartSDK, TCP Client, TCP Server, Serial, FTP, Profinet, Ethernet/IP, MELSEC, ModBus, Fins, SLMP			
Electrical feature				
Data interface	Gigabit Ethernet (1000 Mbit/s)			
Digital I/O	12-pin M12 connector provides power and I/O, including opto-isolated input (LineIn 0/1/2) × 3, opto-isolated output (LineOut 3/4/5) × 3, RS-232 input × 1, and RS-232 output × 1.			
Power supply	24 VDC			
Max. power consumption	60 W @ 24 VDC (light source enabled)			
Mechanical				
Focal length	8 mm	12 mm	16 mm	25 mm
Lens mount	M12-mount, mechanical autofocus supported.			
Lens cap	Half polarization lens cap by default. Transparent and full polarization lens cap are optional.			
Light source	White light by default. Red/blue/IR light is optional.			
Indicator	Power indicator (PWR), network indicator (LNK/ACT), and user-defined indicator (U1/U2).			
Dimension	112.5 mm × 65.5 mm × 63.3 mm (4.4" × 2.6" × 2.5")			
Weight	Approx. 450 g (1.0 lb.)			
Ingress protection	IP67 (under proper installation of waterproof lens cap)			
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)			
Humidity	20% RH to 95% RH (no condensation)			
General				
Client software	IDMVS			
Certification	CE, RoHS, KC			

Detection Range

TP9550-08/12/16/25S-WBN (Unit: mm)

Lens Focal Length	Working Distance	Field of View		1D Single Pixel Accuracy	2D Single Pixel Accuracy	Diagram of Horizontal Field of View
		H	V			
8	25	25.6	20.48	0.010	0.030	
	100	102.4	81.92	0.040	0.120	
	200	204.8	163.84	0.080	0.240	
	300	307.2	245.76	0.120	0.360	
	400	409.6	327.68	0.160	0.480	
	500	512	409.6	0.200	0.600	
	600	614.4	491.52	0.240	0.720	
12	60	40.96	32.77	0.016	0.048	
	100	68.27	54.61	0.027	0.080	
	200	136.53	109.23	0.053	0.160	
	300	204.8	163.84	0.080	0.240	
	400	273.07	218.45	0.107	0.320	
	500	341.33	273.07	0.133	0.400	
	600	409.6	327.68	0.160	0.480	
16	100	51.2	40.96	0.020	0.060	
	200	102.4	81.92	0.040	0.120	
	300	153.6	122.88	0.060	0.180	
	400	204.8	163.84	0.080	0.240	
	500	256	204.8	0.100	0.300	
	600	307.2	245.76	0.120	0.360	
	230	75.37	60.29	0.029	0.088	
25	300	98.3	78.64	0.038	0.115	
	400	131.07	104.86	0.051	0.154	
	500	163.84	131.07	0.064	0.192	
	600	196.61	157.29	0.077	0.230	